



HONGHUA AMERICA, LLC

HH Rotary Table



(832) 448.8100

www.hh-america.com



HONGHUA Group rotary table with 17 ½” to 49 ½” opening size are available.

Main features:

- Conform to the requirements of API Spec. 7K, and industry standard SY/T5531.
- The rotary table adopts spiral bevel gear drive, has higher loading capacity and running smooth, long service life.
- The casing (main frame) is a casting and welding structure, has better rigidity and high precision.
- The gears and bearings adopt splash lubrication, simple and reliable.
- The input shaft is a cartridge structure, convenient to servicing.

Specification

Table 1: specification of rotary table ZP175 & ZP205

	model units	ZP175	ZP205
Opening diameter	in	17.5	20.5
Max. static load	lb	505,820	708,150
Max. working torque	ft. lb	10,126	16,636
Max. speed	rpm	300	300
Gear ratio	-	3.58	3.22
Overall dimension (L*W*H)	in	76.2*50.4*23.0	90.2*58.1*26.3
weight	lb	8,572	12,190
Min. allowed ambient temperature	F	-4°	-4°
Max. allowed ambient temperature	F	122°	122°

More rotary tables' specification please check the table 2 on the next page.





Table 2: specification of rotary table ZP275 & ZP375 & ZP495 (continued)

	model units	ZP275	ZP375	ZP495
Opening diameter	In	27.5	37.5	49.5
Max. static load	lb	1,011,600	1,315,100	1,629,900
Max. working torque	ft.lb	20,252	23,870	26,762
Max. speed	rpm	300	300	300
Gear ratio	-	3.67	3.56	3.93
Overall dimension (L*W*H)	in	94.2*65.7*27.0	97.2*71.2*28.3	115.7*84.6*32
Weight	lb	13,857	16,640	25,631
Min. allowed ambient temperature	F	-40° F	-40° F	-40° F
Max. allowed ambient temperature	F	122° F	122° F	122° F



**We provide HH and LS-NOV rotary tables
*in stock.***

Please contact us if you need more information!

Honghua, America, LLC

8300 McHard Road, Houston, TX 77053

Tel : (832) 448.8100

Fax : (832) 448.8101

E-mail: sales@hh-america.com

Website: www.hh-america.com

